



TG-V26ZD



SOLUTIONS SECURING YOUR WORLD

KEY FEATURES

- 2MP @ 30fps Smart H.265/H.264 IR Starlight motorized Dome Network Camera
- 30 ~ 50m IR night view distance
- 3D DNR, HLC, BLC, Defog, Smart IR & ROI coding
- WDR 120dB
- Starlight
- Support corridor mode
- Built in Mic
- Support 3 streams
- AC24V/DC12V/ PoE power supply
- Supports 128GB microSD storage
- Intelligent analytics
- IP67/IK10

SPECIFICATIONS

Description	2MP @ 30fps H.265+/ H.265/H.264/H.264, IR Starlight Motorized Dome Network Camera	
Camera	Image Sensor	1 / 2.8 "CMOS
	Shutter	1 s ~ 1 / 100000 s
	Minimum Illumination	0.0038 lux@F1.4,AGC ON; 0 lux with IR 0.0028 lux@F1.2,AGC ON; 0 lux with IR
	Day/Night	ICR
	Lens	2.8~12mm@F1.4, motorized
	Digital NR	3D DNR
	IR Distance	Up to 50m
	WDR	120dB
Video	Video Compression	Main stream: Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
	H.264 Compression	Baseline Profile/Main Profile/High Profile
	Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
	Primary Stream	60Hz:1080P/720P(1 ~ 30fps); 50Hz:1080P / 720P(1 ~ 25fps)
	Secondary Stream	60Hz:720P/D1/CIF /480×240 (1~30fps); 50Hz:720P/D1/CIF /480×240 (1~25fps)
	Tertiary Stream	60Hz:D1/CIF 480 240 (1~30fps); 50Hz:/ × D1/CIF/480×240 (1~25fps)
	Bit Rate	64 Kbps ~ 6 Mbps
	Image Settings	ROI, Saturation, Brightness, Hue, Contrast,Wide Dynamic, Sharpness,
	ROI	Each ROI to be configured separately
	Audio	Audio Compression
Audio		1CH audio input; 1CH audio output; Built-in MIC
System	Remote Monitoring	Web browsing,CMS remote control
	Online Connection	Support simultaneous monitoring for up to 10 users;; Support multi-stream real time transmission
	Interface Protocol	ONVIF
	Smart Alarm	Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, cable disconnection
	Intelligent Analytics	Video blur detection, scene change detection, line crossing detection and region, intrusion detection, Face detection and face capture
	Function	Watermark, IP address filtering, video mask, heartbeat, password protection, image distortion correction
Storage	Storage	Network remote storage; micro SD card storage
Network	Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, FTP, PPPoE, DDNS, SMTP,SNMP,HTTP, 802.1x, UPnP, HTTPs, QoS
Interface	Ethernet	1x RJ45 10M/100M Ethernet Port
General	Power	DC12V/PoE
		Power consumption: < 10.5W
	Operating Conditions	- 30 °C ~ 60°C (-22°F~140°F) Humidity: less than 95 % (non condensing)
	Dimensions	141 × 100.2
Weight	Approx.0.89Kg	

ACCESSORIES



PM-V26ZD
Pole Mount




ECB-V26ZD
External Corner Bracket



JB-V26ZD
Junction Box

DIMENSIONS

Structure Diagram



Units : mm

PARTCODE

DESCRIPTION

TG-V26ZD

2MP @ 30fps Motorized 2.8~12mm, H.265+/H.265/H.264+/H.264 Starlight Dome Camera, Color:0.0038Lux @ F1.4, WDR 120dB, IR50m, Supports VCA People Counting, Face Detection, IP67, IK10, PoE/ DC12V/PoE.

UAE Address:
P3-Hamriyah Business Centre
PO Box 50235
Hamriyah Free Zone - Sharjah - UAE.
E-mail: info@tgen5.com
Tel : +97143488459

[HTTPS://TGEN5.COM](https://tgen5.com)